

Modem Router 3G HSPA

Main features

- 3G Wireless Router
- HSPA+ 21,6Mbps Download, 5.76Mbps Upload
- UMTS 2100MHz, GSM 850/900/1800/1900MHz
- Wireless 802.11n 300Mbps a 2.4GHz
- 4 ports LAN RJ45 10/100Mbps
- 1 port RJ11, 1 port USB 2.0, 1 slot for USIM

Note: The client must provide the device with a DATA SIM from a selected telephone operator. This is required for it to work properly.



LED Display

FOR EXTERNAL ENVIRONMENT

Available versions

- LED display
- LED display with network analyzer

Main features

- Visualization: 2-line, 16 alphanumeric characters
- Tipology: pages or scrolling (max. 512 scrolling characters)
- Management: via RS485 to the network analyzer or LAN Ethernet
- Supply: 220 V/50 Hz
- Dimensions: 1500x75x700 mm (WxDxH)
- Weight: 15 Kg



SunGuard Video Display

SIGNAL SPLITTER FOR VIDEO SYSTEMS

Available versions

- SunGuard Video Display
- SunGuard Video Display Wi-Fi

The SG-VIDEO-DISPLAY is connected to a monitor with a VGA port and the internet, it allows display with cyclical trend (about 5 seconds), the various trend-related slides of one or more photovoltaic systems monitored with the SunGuard monitoring system. The data displayed on the monitor are as follows: daily production, total production, saved trees, barrels of equivalent petroleum, weekly production, monthly production, avoided CO₂ emissions, instantaneous power.

Main features

- Power supply: 5Vdc/10W wall mount included
- Operating range: 5°C–50°C
- Communication interfaces: 1 RJ45 Ethernet, 2 RS232, VGA port

